




8000 SERIES HYBRID NVRs AT-A-GLANCE







	32 CHANNELS		
			
Model Number	8732 R	8532 R	8532 S
Base Part Number	28065	28066	28067
Total Inputs	32		
Analog/IP Inputs	16/32		
PoE Ports	0		
Channel Licenses Included	32		
Analog Performance	480 FPS @ 4CIF	240 FPS @ 4CIF	
IP Performance (primary plus alternate stream)	80 Mbps		
Analog Compression	H.264		
Local Area Network	GigE		
Camera Network	GigE		
Analog Resolutions	4CIF/2CIF/CIF		
IP Resolution	Camera dependent		
Operating System	Embedded Linux		
Alarms	8 In / 4 Out		
Audio	4 In / 2 Out		
Local Control	Yes (IP Camera Capable)		
Video Out	HDMI/Composite		
Max HDDs	4		
Max HD Storage	Up to 40 TB		
Storage Redundancy	Mirroring (reduces throughput)		
Data Ports	4 USB, 1 RS-232, 1 RS-485		
Docking Station	Yes		No
Dimensions (H x W x D)	3.1 x 17.4 x 16.0 in (8.0 x 44.2 x 40.6 cm)		3.2 x 16.9 x 16.0 in (8.1 x 43.0 x 40.6 cm)
Environmental	41° to 105° F (5° to 40° C)		
Power Supply	Internal 115/230 VAC (auto-sensing); 75 W max		
Weight (add 5.5 lbs/2.5 Kg for docking station)	18.5 lbs (8.4 Kg)		13 lbs (5.9 Kg)
Battery Backup	Yes		
Mounting Options	Dock, Desk, Wall	Dock, Desk, Wall	Desk, Wall
Front Panel QR Code*	Yes		
Analytics	Included: Motion Detection / Optional: Camera Obstruction Detection, Field of View Change, Trip Wire, Loitering, Presence Detection		

*The QR Code on the front panel contains useful information about the recorder, such as model number and serial number. When the code is scanned using the March Networks GURU smartphone application, this information allows integrators to easily check warranty status, initiate an express RMA, get in-field diagnostics support, review and change recorder IP addresses, register/unregister from the Enterprise Service Manager, and go through SSH to view storage information.

2-year Advance Replacement plan on all Recorders:

- Options for Repair & Return or Advance Replacement
- March Networks incurs all shipping costs—both ways—for AR's
- All NVR components are covered, including HDDs

8000 SERIES HYBRID NVRS AT-A-GLANCE

	16 CHANNELS			8 CHANNELS		4 CHANNELS
						
Model Number	8716 P	8516 R	8516 S	8708 S	8508 S	8704 S
Base Part Number	34246	28646	28068	28570	28568	28569
Total Inputs	16			8		4
Analog/IP Inputs	8/16	16/16		8/8		4/4
PoE Ports	8	0		0		0
Channel Licenses Included	16			8		4
Analog Performance	30 FPS @4CIF	240 FPS @ 4CIF		240 FPS @ 4CIF	120 FPS @ 4CIF	120 FPS @ 4CIF
IP Performance (primary plus alternate stream)	80 Mbps			80 Mbps		80 Mbps
Analog Compression	H.264			H.264		H.264
Local Area Network	GigE			GigE		GigE
Camera Network	10/100 Base-T	GigE		GigE		GigE
Analog Resolutions	4CIF/2CIF/CIF			4CIF/2CIF/CIF		4CIF/2CIF/CIF
IP Resolution	Camera dependent			Camera dependent		Camera dependent
Operating System	Embedded Linux			Embedded Linux		Embedded Linux
Alarms	2 In / 1 Out	8 In / 4 Out		2 In / 1 Out		2 In / 1 Out
Audio	2 In / 1 Out	4 In / 2 Out		2 In / 1 Out		2 In / 1 Out
Local Control	Yes (IP Camera Capable)			Yes (IP Camera Capable)		No
Video Out	HDMI/Composite			HDMI/Composite		No
Max HDDs	2	4		2		2
Max HD Storage	Up to 20 TB	Up to 40 TB		Up to 20 TB		Up to 10 TB
Storage Redundancy	Mirroring (reduces throughput)			Mirroring (reduces throughput)		Mirroring (reduces throughput)
Data Ports	4 USB, 1 RS-232	4 USB, 1 RS-232, 1 RS-485		4 USB, 1 RS-232		2 USB, 1 RS-232
Docking Station	No	Yes	No	No		No
Dimensions (H x W x D)	3.6 x 11.3 x 12.0 in (9.18 x 28.7 x 30.6 cm)	3.1 x 17.4 x 16.0 in (8.0 x 44.2 x 40.6 cm)	3.2 x 16.9 x 16.0 in (8.1 x 43.0 x 40.6 cm)	3.6 x 11.3 x 12.0 in (9.18 x 28.7 x 30.6 cm)		3.2 x 8.3 x 5.0 in (8.1 x 21.2 x 12.6 cm)
Environmental	41° to 105° F (5° to 40° C)			41° to 105° F (5° to 40° C)		41° to 105° F (5° to 40° C)
Power Supply	External 110/220 VAC (auto-sensing); 60 W max	Internal 115/230 VAC (auto-sensing); 75 W max		External 110/220 VAC (auto-sensing); 60 W max		External 110/220 VAC (auto-sensing); 20 W max
Weight (add 5.5 lbs/ 2.5 Kg for docking station)	7.8 lbs (3.6 Kg)	18.5 lbs (8.4 Kg)	13 lbs (5.9 Kg)	7.3 lbs (3.3 Kg)		3.3 lbs (1.5 Kg)
Battery Backup	Yes			Yes		Yes
Mounting Options	Desk, Wall	Dock, Desk, Wall	Desk, Wall	Desk, Wall		Desk, Wall
Front Panel QR Code*	Yes			Yes		Yes
Analytics	Included: Motion Detection / Optional: Camera Obstruction Detection, Field of View Change, Trip Wire, Loitering, Presence Detection					

*The QR Code on the front panel contains useful information about the recorder, such as model number and serial number. When the code is scanned using the March Networks GURU smartphone application, this information allows integrators to easily check warranty status, initiate an express RMA, get in-field diagnostics support, review and change recorder IP addresses, register/unregister from the Enterprise Service Manager, and go through SSH to view storage information.

North America 1 800 563 5564
 Latin America +5255 5259 9511
 Europe +39 0362 17935
 Asia +65 6818 0963
 Australia and New Zealand . . . +61 1300 089 419
 Middle East and Africa +971 4 399 5525

© 2018. March Networks, An Infinova Company. All rights reserved. Information in this document is subject to change without notice. MARCH NETWORKS, March Networks Command, March Networks Searchlight, March Networks RideSafe, and the MARCH NETWORKS logo are trademarks of March Networks Corporation. Infinova is a trademark of Infinova Corporation. All other trademarks are the property of their respective owners. 060-3172-00-G marchnetworks.com

